

SAFETY DATA SHEET HIGH GLOSS TYRE DRESSING

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME HIGH GLOSS TYRE DRESSING
 SUPPLIER Valet Pro Limited
 3 Summervale Road
 Turnbridge Wells
 Kent
 TN4 8JA
 08450 090 134

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
KEROSENE - NARROW CUT - NON AROMATIC		64742-47-8	60-100%	Xn;R65. R66.

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

CLASSIFICATION Xn;R65. R66.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. For breathing difficulties oxygen may be necessary.

INGESTION

DO NOT INDUCE VOMITING! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT

HIGH GLOSS TYRE DRESSING



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid Clear		
COLOUR	colourless		
ODOUR	Characteristic vanilla		
SOLUBILITY	Immiscible with water		
RELATIVE DENSITY	0.824 - 0.834 @ 20 °c	pH-VALUE, CONC. SOLUTION	N/A
FLASH POINT (°C)	>70 CC (Closed cup).		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Irritating gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

Vapour may irritate respiratory system or lungs.

INGESTION

Harmful: may cause lung damage if swallowed.

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not classed as Hazardous to the Environment but release to the environment should be avoided.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

HIGH GLOSS TYRE DRESSING

ROAD TRANSPORT NOTES Not Classified
 SEA TRANSPORT NOTES Not Classified.
 AIR TRANSPORT NOTES Not Classified.
 HAZARD No. (ADR) .

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS KEROSENE - NARROW CUT - NON AROMATIC

RISK PHRASES

R65 Harmful: may cause lung damage if swallowed.
 R66 Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES

S2 Keep out of the reach of children
 S23 Do not breathe vapour/spray.
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S37/39 Wear suitable gloves and eye/face protection.
 S51 Use only in well-ventilated areas.
 S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

GENERAL INFORMATION

The following risk phrases relate to the raw materials in the product and not the product itself:-

REVISION DATE 12/04/2006

REV. NO./REPL. SDS GENERATED 3

RISK PHRASES IN FULL

R65 Harmful: may cause lung damage if swallowed.
 R66 Repeated exposure may cause skin dryness or cracking.